

# SiteWatch PRO3 Smart Security Camera

Up to 13 MP All-Weather Camera for Real-time Monitoring

#### SWPRO3VG-3-10x Camera Kit

#### Flexible, Reliable, Affordable

Sensera Systems' SiteWatch PRO3 day/night site monitoring solution combines thermal/low-light and color cameras with IR illumination, video analytics and 4G LTE communications in one integrated system. This portable smart camera is perfect for 24/7 monitoring capable of real-time alert notifications (pushed to your email or mobile device). All video analytics are executed inside the camera, and only video relating to actual events is sent to the cloud for archival and viewing.















- Works with No Light on Site the thermal imager can detect people and vehicles with zero light, then uses the included IR illuminator to capture detail with the low-light camera.
- **Long Range Detection** the thermal camera provides long-range detection to cover more of the jobsite.
- 3-in-1 Camera System thermal for detection, low-light for capturing detail in the lowest light conditions, and color for daytime and with sufficient ambient lighting. The intelligent system switches between camera sensors automatically to provide the best imagery based on light levels.

#### Access Your Camera 24/7

- 1080p video streaming and recording (configurable)
- Low-light detection with sensitive 4K camera
- Long-range motion detection covers large areas with fewer cameras
- Continuous video recording
- Schedule and automate capture of stills
- NDAA Compliant



## SiteWatch PRO3 Security Camera

### **Technical Specifications**

#### SWPRO3VG-3-10x Camera Kit



CAI	ME	RΑ
-----	----	----

Color/Day Camera

Image Sensor CMOS I3MP Sensor

Resolution

13 Megapixel on demand daytime, 8mp LiveView day, 1920 x 1080 (2mp)

zero-latency triggered day

Resolution (video stream)

640 x 480, 1280 x 720 (720p),

1920 x 1080 (1080p)

Video Compression Daytime Field of View (FoV)

H.264 or MJPEG 74.9°(H) x 59.4°(V)

Resolution (recording)

640 x 480, 1280 x 720, 1920, 1080

High Dynamic Range (HDR)

Day/night HDR for improved image quality under uneven lighting conditions

Low-Light Black & White Camera

Image Sensor

CMOS 4K Sensor

Resolution (still)

8mp on demand night illuminated 8mp LiveView night illuminated

2mp triggered night

Resolution (video stream)

(resolution triggered day/

640 x 480, 1280 x 720, 1920 x 1080

night)

H.264 or MJPEG Video Compression

Minimum Illumination

MJPEG or H.264

 $0.011 \, \text{Lix}$ 

Video Streaming Field of View (FoV)

120 diag 105°(H) x 59°(V)

High Dynamic Range (HDR)

day/night

HDR for improved image quality under uneven lighting conditions

**Thermal Detection Camera** 

Image Sensor

LWIR, 8-14 µm

Resolution (still)

160 x 120

Field of View (FoV)

45 (W) x 56 (diagonal)

Thermal Sensitivity

<50mK

Video Analytics

Thermal Camera Input

Modes

Motion detection with masking

Motion Detection Range

200' x 56°

(Thermal) Masking

Multiple rectangular ignore areas

**Edge Recording** 

Capacity 512GB (up to 137 days)

Recording Resolution

640 x 480, 10/60 second stills or

continuous video

Scheduler (via SiteCloud)

Prefetch

Up to 5 separate schedule segments Automatic uploads of clips on motion

events

**ILLUMINATION** 

Illumination Type IR Power 36W

Illumination Angle

609

**NETWORK** 

Cellular 4G LTE (multiple carriers available)

WiFi 802.11 b/g/n

**GPS** Built-in GPS positioning

**POWER** 

8-24VDC with Maximum Power Point Solar Power Input

Tracking (MPPT)

Solar Panel Included, 35W 31.02" x 13.78" x 1.18"

**Auxiliary Power Input** 18-24VDC

Battery

Integrated rechargeable Lithium Iron Phosphate (LiFePO4), 5 days power

Supply Power

110/220VAC input (a) < 0.74 Amps via

included AC/DC power adapter

Camera Power 18-24VDC @ < 2 Amps

**PHYSICAL** 

Camera Dimensions 7.5"(W) x 6.25" (D) x 8.5" (H)

Camera Weight 7.5 lbs Solar Panel Weight 7.3 lbs

Mounting Hardware Pole/wall mount included

**ENVIRONMENTAL** 

Operating Temperature -20°C (-4°F) to +50°C (122°F)

**Enclosure Material** Polycarbonate Encapsulation All-Weather IP65

SITECLOUD SERVICE RELATED FEATURES

Live streaming video

Video/image recording with web-based upload

Captured image/video archival and viewing

Edge storage: scheduled, configure, retrieve

Event notifications, trigger events via SMS, email, API

Motion detection: video analytics configuration, masking, arming schedules

**ORDERING** 

SWPRO3VG-3-102 RT-SWPRO3VG 3-102-xxxx

SWPRO3VG-03-101

(rental)

SWPRO3 Camera Kit (Solar or AC) Includes camera integrated battery pack, indoor AC adapter, solar panel and mounting brackets. Requires

SWPRO3 Camera Kit (AC Power only) Includes camera, outdoor AC power

SiteCloud Service for operation.

adapter, IR illumination and mounting brackets. Requires SiteCloud for

operation.

Available Carriers Verizon, AT&T, T-Mobile (United States)

Telus and Rogers (Canada).

Cloud Service Cellular plans start at IGB

Optional Accessories Roof Mount Kit, Tripod Kit, 20'

> Telescoping Pole, Portable Solar Trailer, Camera Transport Case, Outdoor AC

Adapter

SPECIFICATIONS SUBJECT TO CHANGE Images are for illustration purposes only

Manufactured in Golden, Colorado

